

09/661,876

dialup modem connection to the Internet, the system is compatible with a local area network and the system is compatible with virtual network connection.

39. (withdrawn) The system of claim 38, wherein the range of access levels ranges from allowing all access to allowing no access at all.

40. (canceled)

41. (withdrawn) A versatile customizable combination system for providing filtering of outbound requests for access to web sites on the Internet, comprising:

- a plurality of computer users,
- one or a plurality of user computers, each having a dynamically allocated Internet protocol address or a static Internet Protocol address,
- an administrative module/interface that includes configuration settings for outbound communications, has list maintenance functions including list editing, list deleting, searching of lists, saving of lists, proxy chaining routing, adding and deleting users, interchanging lists and importing and exporting lists,
- said administrative module located in a user computer for configuring a range of access levels and being capable of creating three types of user accounts that require unique authentication credentials for each user account including an administrator account that is self-configuring, ~~and~~ regular accounts with administrative privileges other than the privilege to create additional accounts or view information on any other accounts and regular accounts without administrative privileges,

09/661,876

a first proxy server in one or a plurality of user computers of a local area network with access to the world wide web, each of said first proxy server having a friendly outbound list and/or an unfriendly outbound list only one of which is active at any given time, the friendly outbound list and the unfriendly outbound list being uniquely configurable for each user account,

said first proxy server programmed to receive a request from an HTTP client, check the identity of a requested URL against the friendly outbound list or unfriendly outbound list maintained by the administrative module and then either approve the request, terminate the request or re-route the request,

a second proxy server without the administrative module or the friendly or the unfriendly lists placed between the first proxy server and the Internet, the second proxy server being capable of communicating to a proxy of a destination or directly to a destination, said second proxy server having an Internet Protocol address configurable only by a holder of the administrator account or a regular account with administrative privileges,

the first proxy server programmed to forward the request to the second proxy

PAGE 3/3 * RCVD AT 12/18/2008 7:30:45 PM [Eastern Standard Time] * SVR:USPTO-EFXXRF-4/17 * DNIS:2738300 * CSID: * DURATION (mm-ss):09-50

BEST AVAILABLE COPY